

DECKSUPPORT

EUROPEAN FINGERJOINT SUPPORT FOR DECKING

GENERAL DESCRIPTION

Wood slats, manufactured in finger joint assembled elements (300 to 900 mm long, with tolerance $\pm 5\%$), glued and pressed in high pressure, to ensure a high flexion resistance (similar to the lumber one). All cracks and faulty knots are removed. Profiled E4E.

SIZES

Long*	Width**	Thickness**
2000 - 6000 mm	65 mm	40 mm
2000 - 6000 mm	60 mm	40 mm
2000 - 6000 mm	60 mm	30 mm ***
2000 - 6000 mm	40 mm	40mm
2000 - 6000 mm	53 mm	33 mm

* Tolerance - 5mm, +15 to 30mm.

** Tolerance in width and thickness ± 1 mm

*** Special size for composite deck.



WOOD SPECIES

Piquia, angelim pedra, Tatajuba, Itauba, Massaranduba, red eucalyptus, garapa and other species suitable for outdoor.

ADVANTAGES

- Fixed length for easy installation.
- Stable sticks, avoid deformations such as warpage and twisting in solid wood.

USES

- Product suitable as a support for decking and cladding (wall and roof) for exteriors.

QUALITY

- Accepted finger joint space up to 1.5mm.
- Accepted fiber picking, and minor profiling faults.
- Accepted difference in colors in same board.

TECHNICAL SPECIFICATIONS

- Adhesives of double component for industrial applications of wood.
- Tests bending resistance similar to the strength of a lumber.
- The aging of the wood does not alter the strength of the joint.

SPECIFIQUE DECKSUPPORTS SALES CONDITIONS

Add to general sales condition, Claims for product specifications and tolerances described in this document are not accepted. Other claims should be presented within 72 hours from reception of goods.

Manufactured in Spain



www.fustakia.com

Technical specifications support for decking
Rev. 3 11-2016